

View Online at <https://aerobasegroup.com/nsn/5999-00-938-2237>

Thread Class:

2b

Thread Pitch Diameters:

+0.1257/+0.1437 inches

Body Style:

Rectangular

Frequency Rating:

Between 3.000 kilohertz and 6.000 kilohertz

Body Length:

Between 4.094 inches and 4.156 inches

Body Width:

Between 2.969 inches and 3.031 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

Between 3.734 inches and 3.766 inches

Longest Vertical Distance Between Mounting Centers:

Between 2.234 inches and 2.266 inches

Operating Temperature Range:

-5.0/+75.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

10.000 volts

Surface Treatment And Location:

Paint, zinc chromate primer, jan-p-735 fscm 81349 body

Input Impedance Rating:

1.500 kilohms

Output Impedance Rating:

750.000 ohms

Frequency Bandwidth:

3.000 kilohertz

Body Depth:

Between 2.594 inches and 2.656 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

334.900 microseconds single section

Segment Quantity Per Section:

33 single section

Terminal Type And Quantity:

36 wire hook

Special Features:

Hermetically sealed case

Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100