

View Online at <https://aerobasegroup.com/nsn/5999-00-938-8615>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.1875/+0.1876 inches

**Body Style:**

Rectangular

**Frequency Rating:**

16.500 kilohertz

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Slotted screw

**Body Length:**

3.255 inches

**Body Width:**

3.942 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.700 inches

**Longest Vertical Distance Between Mounting Centers:**

2.500 inches

**Operating Temperature Range:**

+0.0/+60.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

20.000 volts

**Input Impedance Rating:**

500.000 ohms

**Output Impedance Rating:**

1.500 kilohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.460 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

337.500 microseconds single section err-100

**Delay Time Variation Per Deg Celsius:**

0.417 nanoseconds

**Pulse Rise Time Rating:**

150.0 nanoseconds

**Terminal Type And Quantity:**

5 pin

**Special Features:**

Cased hermetically sealed construction

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100