NSN 5999-00-940-0281



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-940-0281 **Body Style:** Rectangular, bracketed **Hole Diameter:** 0.250 inches **Overall Length:** 13.500 inches **Body Length:** 12.000 inches **Body Width:** 5.250 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 12.750 inches **Longest Vertical Distance Between Mounting Centers:** 8.000 inches **Operating Tempurature Range:** +15.0/+45.0 degrees celsius **Mounting Facility Quantity: Material And Location:** Brass terminal err-100 err-100 **Surface Treatment And Location:** Enamel, mil-e-15090, type 3, class 2 case err-100 err-100 Input Impedance Rating: 510.000 ohms **Output Impedance Rating:** Not rated **Body Depth:** 8.750 inches **Mounting Facility:** Unthreaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 3.000 **Signal Delay Method:** Electromechanical **Delay Time Variation Method:**

Tapped

Section Delay Time:

3.200 milliseconds single section

NSN 5999-00-940-0281

Delay Line - Page 2 of 2

Yes - demil/mli

Fiig: A32100



Segment Quantity Per Section:
80 single section
Segment Delay Time:
40.000 microseconds single section all segments
Delay Time Variation Per Deg Celsius:
Not rated
Terminal Type And Quantity:
94 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: