NSN 5999-00-945-3856



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-945-3856 **Thread Class:** 2b **Thread Pitch Diameters:** +0.0920/+0.0950 inches **Body Style:** Rectangular, front connection **Overall Depth:** 0.875 inches Frequency Rating: Not rated **Body Length:** 4.750 inches **Body Width:** 1.062 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 3.000 inches **Operating Tempurature Range:** -30.0/+65.0 degrees celsius **Mounting Facility Quantity:** 2 **Voltage Rating:** 2.000 volts Input Impedance Rating: 510.000 ohms **Output Impedance Rating:** 510.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.562 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** 2.000 **Signal Delay Method:**

Section Delay Time:

Electromechanical

0.892 microseconds single section err-100

NSN 5999-00-945-3856

Delay Line - Page 2 of 2



Delay Time Variation Per Deg Celsius:
300.000 microseconds
Pulse Rise Time Rating:
0.040 microseconds
Terminal Type And Quantity:
3 pin
Thread Size And Series/type Designator:
0.112-40 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A32100