

View Online at <https://aerobasegroup.com/nsn/5999-00-950-8841>

**Thread Class:**

2b

**Body Style:**

Rectangular

**Frequency Rating:**

1.000 megahertz

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Slotted screw

**Body Length:**

5.000 inches

**Body Width:**

3.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

4.250 inches

**Operating Temperature Range:**

+0.0/+70.0 degrees celsius

**Mounting Facility Quantity:**

2

**Voltage Rating:**

60.000 volts

**Material And Location:**

Steel, qq-s-763, class 316l case

**Surface Treatment And Location:**

Enamel, mil-e-15090, type 3, class 2 case

**Frequency Bandwidth:**

1000.0 kilohertz

**Body Depth:**

0.625 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

50.000

**Signal Delay Method:**

Lumped constant

**Section Delay Time:**

377.000 microseconds single section

**Terminal Type And Quantity:**

5 tab solder lug

**Test Data Document:**

10001-1651048 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Size And Series/type Designator:**

0.164-32 unc

**Fsc Application Data:**

Weapons direction equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100