

View Online at <https://aerobasegroup.com/nsn/5999-00-950-8841>

Thread Class:

2b

Body Style:

Rectangular

Frequency Rating:

1.000 megahertz

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Slotted screw

Body Length:

5.000 inches

Body Width:

3.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Mounting Facility Quantity:

2

Voltage Rating:

60.000 volts

Material And Location:

Steel, qq-s-763, class 316l case

Surface Treatment And Location:

Enamel, mil-e-15090, type 3, class 2 case

Frequency Bandwidth:

1000.0 kilohertz

Body Depth:

0.625 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

50.000

Signal Delay Method:

Lumped constant

Section Delay Time:

377.000 microseconds single section

Terminal Type And Quantity:

5 tab solder lug

Test Data Document:

10001-1651048 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Weapons direction equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100