## NSN 5999-00-950-8842

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-950-8842 **Thread Class:** 2b **Body Style:** Rectangular **Body Length:** 5.000 inches **Body Width:** 0.625 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 4.250 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Mounting Facility Quantity: Material And Location:** Steel case **Surface Treatment And Location:** Enamel, mil-e-15090, type 3, class 2 case **Body Depth:** 3.500 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** 50.000 Signal Delay Method: Inductance **Section Delay Time:** 452.000 microseconds single section **Terminal Type And Quantity:** 5 tab solder lug **Test Data Document:** 10001-16501048 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Thread Size And Series/type Designator:

0.164-32 unc

**Fsc Application Data:** 

Weapons direction equipment

Shelf Life:

N/a

## NSN 5999-00-950-8842

Delay Line - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100