NSN 5999-00-950-9411

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-950-9411

Thread	Class:	

- 2b
- Body Style:
- Rectangular
- Body Length:
- 5.000 inches
- Body Width:
- 0.625 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Operating Tempurature Range:

+0.0/+70.0 degrees celsius

Mounting Facility Quantity:

2

Material And Location:

Steel case

Surface Treatment And Location:

Enamel, mil-e-15090, type 3, class 2 case

Body Depth:

3.500 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

50.000

Signal Delay Method:

Inductance

Section Delay Time:

77.000 microseconds single section

Terminal Type And Quantity:

5 tab solder lug

Test Data Document:

10001-1651048 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Weapons direction equipment

Shelf Life:

NSN 5999-00-950-9411

Delay Line - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100

