NSN 5999-00-950-9412

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-950-9412

| Thread Class: |
|--|
| 2b |
| Body Style: |
| Rectangular |
| Body Length: |
| 5.000 inches |
| Body Width: |
| 0.625 inches |
| Individual Section Quantity: |
| 1 |
| Longest Horizontal Distance Between Mounting Centers: |
| 4.250 inches |
| Operating Tempurature Range: |
| +0.0/+70.0 degrees celsius |
| Mounting Facility Quantity: |
| 2 |
| Material And Location: |
| Steel case |
| Surface Treatment And Location: |
| Enamel, dull gray, metallic case |
| Frequency Bandwidth: |
| 1500.0 kilohertz |
| Body Depth: |
| 3.500 inches |
| Mounting Facility: |
| Threaded hole |
| Mounting Provision Arrangement Style: |
| 2 position in-line |
| Attenuation In Decibels: |
| 50.000 |
| Signal Delay Method: |
| Inductance |
| Section Delay Time: |
| 152.000 microseconds single section |
| Terminal Type And Quantity: |
| 5 tab solder lug |
| Test Data Document: |
| 10001-1651048 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| |

Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Weapons direction equipment

NSN 5999-00-950-9412

Delay Line - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100

