NSN 5999-00-965-6263

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-965-6263

Thread Class:
2b
Body Style:
Rectangular
Body Length:
5.000 inches
Body Width:
0.625 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
4.250 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Mounting Facility Quantity:
2
Material And Location:
Steel case
Surface Treatment And Location:
Enamel, mil-e-15090, type 3, class 2 case
Body Depth:
3.500 inches
Mounting Facility:
Threaded hole
Mounting Provision Arrangement Style:
2 position in-line
Attenuation In Decibels:
50.000
Signal Delay Method:
Inductance
Section Delay Time:
527.000 microseconds single section
Terminal Type And Quantity:
5 tab solder lug
Test Data Document:
10001-1651048 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Size And Series/type Designator:
0.164-32 unc
Fsc Application Data:

Target designating equipment

Shelf Life:

N/a

NSN 5999-00-965-6263

Delay Line - Page 2 of 2



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100