

View Online at <https://aerobasegroup.com/nsn/5999-00-973-0667>

Thread Class:

2a

Thread Pitch Diameters:

+0.1141/+0.1169 inches

Body Style:

Rectangular

Body Length:

3.750 inches

Body Width:

1.880 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.125 inches

Longest Vertical Distance Between Mounting Centers:

1.375 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Stud Length:

0.470 inches

Mounting Facility Quantity:

4

Material And Location:

Steel

Surface Treatment And Location:

Tin plated, mil-t-10727, type 1 terminal

Input Impedance Rating:

1.200 kilohms

Output Impedance Rating:

1.200 kilohms

Body Depth:

1.630 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

6.000

Signal Delay Method:

Electromechanical

Section Delay Time:

10.000 microseconds single section

Pulse Rise Time Rating:

300.0 nanoseconds

Terminal Type And Quantity:

3 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar set, guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A32100