

View Online at <https://aerobasegroup.com/nsn/5999-00-973-6223>

Thread Class:

2b

Body Style:

Rectangular

Frequency Rating:

16.500 kilohertz

Adjustment Device Quantity:

2

Adjustment Device Drive Type:

Slotted screw

Body Length:

3.400 inches

Body Width:

3.255 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

2.700 inches

Longest Vertical Distance Between Mounting Centers:

2.500 inches

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

20.000 volts

Material And Location:

Aluminum alloy case

Surface Treatment And Location:

Enamel, dull gray, metallic case

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

0.460 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

32.000 microseconds 2nd section err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

150.0 nanoseconds

Terminal Type And Quantity:

8 pin

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radar set fire control nonairborne

Reference Number Differentiating Characteristics:

Quality controlled and selected

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100