

View Online at <https://aerobasegroup.com/nsn/5999-00-973-6223>

**Thread Class:**

2b

**Body Style:**

Rectangular

**Frequency Rating:**

16.500 kilohertz

**Adjustment Device Quantity:**

2

**Adjustment Device Drive Type:**

Slotted screw

**Body Length:**

3.400 inches

**Body Width:**

3.255 inches

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

2.700 inches

**Longest Vertical Distance Between Mounting Centers:**

2.500 inches

**Operating Temperature Range:**

+0.0/+60.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

20.000 volts

**Material And Location:**

Aluminum alloy case

**Surface Treatment And Location:**

Enamel, dull gray, metallic case

**Input Impedance Rating:**

500.000 ohms

**Output Impedance Rating:**

500.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.460 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

32.000 microseconds 2nd section err-100

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

150.0 nanoseconds

**Terminal Type And Quantity:**

8 pin

**Thread Size And Series/type Designator:**

0.138-32 unc

**Fsc Application Data:**

Radar set fire control nonairborne

**Reference Number Differentiating Characteristics:**

Quality controlled and selected

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100