

View Online at <https://aerobasegroup.com/nsn/5999-00-986-7372>

**Body Style:**

Rectangular, bracketed

**Hole Diameter:**

0.146 inches

**Overall Length:**

8.000 inches

**Frequency Rating:**

50.000 kilohertz

**Body Length:**

8.000 inches

**Body Width:**

0.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.375 inches

**Longest Vertical Distance Between Mounting Centers:**

7.250 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

5.000 volts

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

75.000 ohms

**Output Impedance Rating:**

75.000 ohms

**Frequency Bandwidth:**

18000.0 kilohertz

**Body Depth:**

1.000 inches

**Mounting Facility:**

Unthreaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

1.000

**Signal Delay Method:**

Lumped constant

**Section Delay Time:**

300.000 nanoseconds single section

**Pulse Rise Time Rating:**

20.0 nanoseconds

**Terminal Type And Quantity:**

3 wire hook

**Fsc Application Data:**

Data display groups communications control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100