

View Online at <https://aerobasegroup.com/nsn/5999-00-994-0284>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1140/+0.1170 inches

**Body Style:**

Rectangular

**Body Length:**

3.380 inches

**Body Width:**

1.080 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.250 inches

**Longest Vertical Distance Between Mounting Centers:**

2.630 inches

**Operating Temperature Range:**

-54.0/+125.0 degrees celsius

**Stud Length:**

0.470 inches

**Mounting Facility Quantity:**

2

**Voltage Rating:**

120.000 volts

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

6.200 kilohms

**Output Impedance Rating:**

6.200 kilohms

**Body Depth:**

0.770 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position diagonal

**Signal Delay Method:**

Lumped constant

**Section Delay Time:**

4.500 microseconds single section

**Pulse Rise Time Rating:**

4.5 microseconds

**Terminal Type And Quantity:**

3 solder stud

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100