

View Online at <https://aerobasegroup.com/nsn/5999-00-998-8775>

**Thread Class:**

2a

**Body Style:**

Rectangular

**Shaft Diameter:**

0.250 inches

**Bushing Length:**

0.313 inches

**Shaft Length:**

0.625 inches

**Frequency Rating:**

70.000 megahertz

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Shaft

**Body Length:**

5.375 inches

**Body Width:**

1.250 inches

**Shaft Style:**

Round, slotted

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Stud Length:**

0.500 inches

**Mounting Facility Quantity:**

1 and 4

**Input Impedance Rating:**

93.000 ohms

**Output Impedance Rating:**

93.000 ohms

**Body Depth:**

1.000 inches

**Mounting Facility:**

Threaded bushing and threaded stud

**Attenuation In Decibels:**

3.000

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

50.000 nanoseconds single section err-100

**Pulse Rise Time Rating:**

5.0 nanoseconds

**Terminal Type And Quantity:**

4 wire hook

**Thread Size And Series/type Designator:**

0-375-32 unef and 0.164-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100