## NSN 5999-00-998-8785



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-998-8785 **Thread Class:** 2b **Body Style:** Rectangular **Adjustment Device Quantity: Adjustment Device Drive Type:** Slotted screw **Body Length:** 2.450 inches **Body Width:** 1.030 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.800 inches **Longest Vertical Distance Between Mounting Centers:** 2.200 inches **Operating Tempurature Range:** -40.0/+85.0 degrees celsius **Mounting Facility Quantity:** 2 Input Impedance Rating: 200.000 ohms **Output Impedance Rating:** 200.000 ohms **Body Depth:** 0.310 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** 2 position diagonal **Attenuation In Decibels:** 1.000 **Delay Time Variation Method:** Variable 40.000 nanoseconds single section err-100

Section Delay Time:
40.000 nanoseconds single section errepulse Rise Time Rating:
10.0 nanoseconds
Terminal Type And Quantity:
4 wire leads

## NSN 5999-00-998-8785

Delay Line - Page 2 of 2



0.086-56 unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100