NSN 5999-01-005-5133

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-005-5133

Body Style: Rectangular, top connection Hole Diameter: 0.175 inches Overall Width: 1.300 inches Adjustment Device Quantity: 1 Adjustment Device Drive Type: Slotted screw Body Length: 2.250 inches Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Hole Diameter: 0.175 inches Overall Width: 1.300 inches Adjustment Device Quantity: 1 Adjustment Device Drive Type: Slotted screw Body Length: 2.250 inches Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Overall Width: 1.300 inches Adjustment Device Quantity: 1 Adjustment Device Drive Type: Slotted screw Body Length: 2.250 inches Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Overall Width: 1.300 inches Adjustment Device Quantity: 1 Adjustment Device Drive Type: Slotted screw Body Length: 2.250 inches Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
1.300 inches Adjustment Device Quantity: 1 Adjustment Device Drive Type: Slotted screw Body Length: 2.250 inches Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Adjustment Device Quantity: Adjustment Device Drive Type: Slotted screw Body Length: 2.250 inches Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Adjustment Device Drive Type: Slotted screw Body Length: 2.250 inches Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Adjustment Device Drive Type: Slotted screw Body Length: 2.250 inches Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Slotted screw Body Length: 2.250 inches Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Body Length: 2.250 inches Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
2.250 inches Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Body Width: 0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
0.300 inches Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Longest Horizontal Distance Between Mounting Centers: 1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
1.000 inches Mounting Facility Quantity: 4 Material And Location: Aluminum
Mounting Facility Quantity: 4 Material And Location: Aluminum
4 Material And Location: Aluminum
Material And Location: Aluminum
Aluminum
Body Depth:
0.300 inches
Mounting Facility:
Plug-in
Mounting Provision Arrangement Style:
2 position in-line
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
125.000 nanoseconds single section
Terminal Type And Quantity:
4 wire leads
Fsc Application Data:
Miscellaneous communication equipment
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5999-01-005-5133

Delay Line - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32100