NSN 5999-01-009-1503

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-009-1503

Thread Class:
2a
Body Style:
Rectangular
Frequency Rating:
Not rated
Body Length:
Between 3.375 inches and 3.625 inches
Body Width:
Between 1.062 inches and 1.187 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
2.700 inches
Operating Tempurature Range:
-25.0/+105.0 degrees celsius
Mounting Facility Quantity:
2
Voltage Rating:
Not rated
Material And Location:
Plastic body
Input Impedance Rating:
550.000 ohms
Output Impedance Rating:
550.000 ohms
Frequency Bandwidth:
Not rated
Body Depth:
Between 0.437 inches and 0.562 inches
Mounting Provision Arrangement Style:
2 position in-line
Attenuation In Decibels:
3.000
Signal Delay Method:
Lumped constant
Section Delay Time:
2.000 microseconds single section
Segment Quantity Per Section:
2 single section
Segment Delay Time:
195.000 nanoseconds single section 1st segment err-100

NSN 5999-01-009-1503

Delay Line - Page 2 of 2



Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

150.0 nanoseconds

Terminal Type And Quantity:

5 wire leads

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100