NSN 5999-01-009-1503

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-009-1503 **Thread Class:** 2a **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** Between 3.375 inches and 3.625 inches **Body Width:** Between 1.062 inches and 1.187 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.700 inches **Operating Tempurature Range:** -25.0/+105.0 degrees celsius **Mounting Facility Quantity:** 2 Voltage Rating: Not rated **Material And Location:** Plastic body Input Impedance Rating: 550.000 ohms **Output Impedance Rating:** 550.000 ohms Frequency Bandwidth: Not rated **Body Depth:** Between 0.437 inches and 0.562 inches **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** 3.000 **Signal Delay Method:** Lumped constant **Section Delay Time:** 2.000 microseconds single section **Segment Quantity Per Section:** 2 single section **Segment Delay Time:** 195.000 nanoseconds single section 1st segment err-100

NSN 5999-01-009-1503Delay Line - Page 2 of 2



Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
150.0 nanoseconds
Terminal Type And Quantity:
5 wire leads
Thread Size And Series/type Designator:
0.112-40 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A32100