NSN 5999-01-009-6497



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-009-6497 **Body Style:** Rectangular **Body Length:** 0.620 inches **Body Width:** 0.620 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.400 inches **Longest Vertical Distance Between Mounting Centers:** 0.400 inches **Operating Tempurature Range:** -20.0/+70.0 degrees celsius **Cubic Measure:** 0.215 cubic inches **Inclosure Type: Encased Mounting Facility Quantity: Material And Location:** Any acceptable body **Surface Treatment And Location:** Gold, mil-g-45204, type 2, class 2 terminal Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms Frequency Bandwidth: 5000.0 kilohertz **Body Depth:** 0.450 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 1.000 **Signal Delay Method:**

Inductance

Section Delay Time:

20.000 nanoseconds single section

NSN 5999-01-009-6497

Delay Line - Page 2 of 2



Pulse Rise Time Rating:
5.7 nanoseconds

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32100