NSN 5999-01-016-8763



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-016-8763 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 1.100 inches **Body Width:** 0.460 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.900 inches **Longest Vertical Distance Between Mounting Centers:** 0.260 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity:** Voltage Rating: 3.000 volts **Material And Location:** Plastic body Input Impedance Rating: 300.000 ohms **Output Impedance Rating:** 300.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.200 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** Not rated

Signal Delay Method:
Inductance
Delay Time Variation Method:
Tapped
Section Delay Time:
100.000 nanoseconds single section

NSN 5999-01-016-8763

Delay Line - Page 2 of 2

Fiig: A32100



Segment Quantity Per Section:
6 single section
Segment Delay Time:
20.000 nanoseconds single section 6th segment err-100
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
Not rated
Terminal Type And Quantity:
9 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli