

View Online at <https://aerobasegroup.com/nsn/5999-01-024-8217>

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

0.770 inches

**Body Width:**

0.290 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Voltage Rating:**

50.000 volts

**Material And Location:**

Copper terminal err-100 err-100 or half hard phosphor bronze, terminal or half hard kovar, terminal

**Surface Treatment And Location:**

Tin plate, mil-t-10727, type 1 or 2 terminal err-100 err-100 or half hard tin plated, terminal

**Input Impedance Rating:**

200.000 ohms

**Output Impedance Rating:**

200.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.265 inches

**Mounting Facility:**

Pin

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

47.500 nanoseconds single section and 52.500 nanoseconds single section

**Segment Quantity Per Section:**

10 single section

**Segment Delay Time:**

4.000 nanoseconds single section all segments and 6.000 nanoseconds single section all segments

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

13 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100