

View Online at <https://aerobasegroup.com/nsn/5999-01-028-2076>

**Body Style:**

Rectangular

**Hole Diameter:**

Between 0.250 inches and 0.262 inches

**Frequency Rating:**

Not rated

**Body Length:**

Between 4.720 inches and 4.780 inches

**Body Width:**

Between 0.970 inches and 1.030 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

Between 3.220 inches and 3.280 inches

**Longest Vertical Distance Between Mounting Centers:**

Between 0.470 inches and 0.530 inches

**Operating Temperature Range:**

+0.0/+65.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Material And Location:**

Metal

**Surface Treatment And Location:**

Enamel, mil-e-15090, type 2

**Input Impedance Rating:**

100.000 ohms

**Output Impedance Rating:**

100.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

Between 1.220 inches and 1.280 inches

**Mounting Facility:**

Unthreaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

3.000

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

27.000 microseconds single section and 33.000 microseconds single section

**Segment Quantity Per Section:**

10 single section

**Segment Delay Time:**

9.300 microseconds single section 3rd segment err-100 and 9.900 microseconds single section 3rd segment err-100

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

0.1 microseconds

**Terminal Type And Quantity:**

12 wire leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100