## NSN 5999-01-030-2475

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-030-2475 **Body Style:** Rectangular, front connection **Overall Depth:** 2.500 inches **Body Length:** 6.500 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 3.000 inches **Shortest Horizontal Distance Between Mounting Centers:** 1.875 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Mounting Facility Quantity: Surface Treatment And Location:** Enamel, mil-e-15090, type 2, class 2 **Body Depth:** 2.000 inches **Mounting Facility:** Threaded stud **Attenuation In Decibels:** 3.000 **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:** 24.650 microseconds single section **Segment Quantity Per Section:** 4 single section **Segment Delay Time:** 20.300 microseconds single section 1st segment err-100 **Terminal Type And Quantity:** 6 turret **Fsc Application Data:** Radar set, jetds type no an/tps43-e Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5999-01-030-2475

Delay Line - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32100