NSN 5999-01-030-2475

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-030-2475

Body Style:

Rectangular, front connection

Overall Depth:

2.500 inches

Body Length:

6.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Shortest Horizontal Distance Between Mounting Centers:

1.875 inches

Operating Tempurature Range:

-55.0/+85.0 degrees celsius

Mounting Facility Quantity:

6

Surface Treatment And Location:

Enamel, mil-e-15090, type 2, class 2

Body Depth:

2.000 inches

Mounting Facility:

Threaded stud

Attenuation In Decibels:

3.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

24.650 microseconds single section

Segment Quantity Per Section:

4 single section

Segment Delay Time:

20.300 microseconds single section 1st segment err-100

Terminal Type And Quantity:

6 turret

Fsc Application Data:

Radar set, jetds type no an/tps43-e

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5999-01-030-2475

Delay Line - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A32100

