

View Online at <https://aerobasegroup.com/nsn/5999-01-033-6341>

**Body Style:**

Rectangular, bracketed

**Slot Length:**

0.250 inches

**Overall Length:**

4.500 inches

**Flat Height:**

0.216 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.500 inches

**Flatted Portion Length:**

0.250 inches

**Frequency Rating:**

Not rated

**Adjustment Device Quantity:**

2

**Adjustment Device Drive Type:**

Shaft

**Body Length:**

3.500 inches

**Body Width:**

2.250 inches

**Shaft Style:**

Round, flatted

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.750 inches

**Longest Vertical Distance Between Mounting Centers:**

4.000 inches

**Operating Temperature Range:**

-0.0/+70.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Not rated

**Material And Location:**

Aluminum body

**Surface Treatment And Location:**

Enamel, gray body

**Input Impedance Rating:**

100.000 ohms

**Output Impedance Rating:**

100.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

Any acceptable

**Mounting Facility:**

Slotted hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

3.500

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

6.400 microseconds single section

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

250.0 nanoseconds

**Terminal Type And Quantity:**

2 coaxial receptacle and 2 wire hook

**Err Default:**

Err default

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100