

View Online at <https://aerobasegroup.com/nsn/5999-01-033-6341>

Body Style:

Rectangular, bracketed

Slot Length:

0.250 inches

Overall Length:

4.500 inches

Flat Height:

0.216 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

Flatted Portion Length:

0.250 inches

Frequency Rating:

Not rated

Adjustment Device Quantity:

2

Adjustment Device Drive Type:

Shaft

Body Length:

3.500 inches

Body Width:

2.250 inches

Shaft Style:

Round, flatted

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.750 inches

Longest Vertical Distance Between Mounting Centers:

4.000 inches

Operating Temperature Range:

-0.0/+70.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Material And Location:

Aluminum body

Surface Treatment And Location:

Enamel, gray body

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

Any acceptable

Mounting Facility:

Slotted hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

3.500

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

Section Delay Time:

6.400 microseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

250.0 nanoseconds

Terminal Type And Quantity:

2 coaxial receptacle and 2 wire hook

Err Default:

Err default

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100