

View Online at <https://aerobasegroup.com/nsn/5999-01-038-0515>

Thread Class:

2a

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

5.000 inches

Body Width:

3.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.000 inches

Longest Vertical Distance Between Mounting Centers:

Between 3.990 inches and 4.010 inches

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Stud Length:

0.380 inches

Mounting Facility Quantity:

4

Voltage Rating:

30.000 volts

Input Impedance Rating:

10.000 kilohms

Output Impedance Rating:

1.000 kilohms

Frequency Bandwidth:

Between 700.0 hertz and 2500.0 hertz

Body Depth:

1.500 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

35.000

Delay Time Variation Method:

Tapped

Section Delay Time:

566.600 microseconds single section

Segment Quantity Per Section:

5 single section

Segment Delay Time:

563.350 microseconds single section 5th segment err-100 and 569.850 microseconds single section 5th segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

9 turret

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100