NSN 5999-01-038-1236

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-038-1236

Body Style:

Rectangular

Hole Diameter:

0.020 inches

Frequency Rating:

Not rated

Body Length:

1.260 inches

Body Width:

0.510 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.610 inches

Shortest Horizontal Distance Between Mounting Centers:

0.600 inches

Longest Vertical Distance Between Mounting Centers:

0.300 inches

Operating Tempurature Range:

-0.0/+70.0 degrees celsius

Mounting Facility Quantity:

14

Voltage Rating:

Not rated

Input Impedance Rating:

210.000 ohms

Output Impedance Rating:

210.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

0.350 inches

Mounting Facility:

Pin

Mounting Provision Arrangement Style:

Three position off-set

Attenuation In Decibels:

5.000

Signal Delay Method:

Lumped constant

Section Delay Time:

70.000 nanoseconds single section

NSN 5999-01-038-1236

Delay Line - Page 2 of 2



Delay Time Variation Per Deg Celsius:

5.000 nanoseconds

Pulse Rise Time Rating:

18.0 nanoseconds

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100