NSN 5999-01-038-1236



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-038-1236 **Body Style:** Rectangular **Hole Diameter:** 0.020 inches Frequency Rating: Not rated **Body Length:** 1.260 inches **Body Width:** 0.510 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.610 inches **Shortest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -0.0/+70.0 degrees celsius **Mounting Facility Quantity:** 14 **Voltage Rating:** Not rated Input Impedance Rating: 210.000 ohms **Output Impedance Rating:** 210.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.350 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Three position off-set **Attenuation In Decibels:** 5.000

Signal Delay Method:
Lumped constant
Section Delay Time:

Section Delay Time:

70.000 nanoseconds single section

NSN 5999-01-038-1236

Delay Line - Page 2 of 2



Delay Time Variation Per Deg Celsius:
5.000 nanoseconds
Pulse Rise Time Rating:
18.0 nanoseconds
Terminal Type And Quantity:
14 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

Fiig: A32100