NSN 5999-01-040-3632

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-040-3632

Body Style:
Rectangular
Frequency Rating:
Not rated
Body Length:
0.785 inches
Body Width:
0.300 inches
Individual Section Quantity:
1
Operating Tempurature Range:
Not rated
Inclosure Type:
Hermetically sealed
Voltage Rating:
Not rated
Material And Location:
Copper terminal err-100 err-100 or phosphor bronze terminal err-100 err-100
Surface Treatment And Location:
Tin plated terminal
Input Impedance Rating:
100.000 ohms
Output Impedance Rating:
100.000 ohms
Frequency Bandwidth:
Not rated
Body Depth:
0.225 inches
Mounting Facility:
Terminal
Attenuation In Decibels:
0.500
Signal Delay Method:
Lumped constant
Section Delay Time:
100.000 nanoseconds single section
Segment Quantity Per Section:
10 single section
Segment Delay Time:
10.000 nanoseconds single section all segments
Delay Time Variation Per Deg Celsius:

Not rated

NSN 5999-01-040-3632

Delay Line - Page 2 of 2



Pu	lse	Rise	Time	Rating	1:

13.5 nanoseconds

Terminal Type And Quantity:

14 tab solder lug

Fsc Application Data:

An/gsn-t3 training set

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100