

View Online at <https://aerobasegroup.com/nsn/5999-01-040-3655>

**Cross Sectional Shape:**

Mesh and composition

**Hole Diameter:**

Between 0.406 inches and 0.416 inches

**Overall Length:**

Between 13.219 inches and 13.281 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit

**Overall Width:**

Between 5.907 inches and 5.969 inches

**Minor Width:**

0.203 inches

**Inside Corner Radius:**

0.047 inches

**Outside Corner Radius:**

0.250 inches

**Aperture Width:**

2.437 inches

**Aperture Length:**

9.750 inches

**Center To Center Distance Between Bolt Holes Along Width:**

2.218 inches

**Center To Center Distance Between Bolt Holes Along Length:**

2.000 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

0.781 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

0.781 inches

**Cross-sectional Height:**

0.165 inches

**Minor Height:**

0.165 inches

**Bolt Hole Quantity:**

16

**Environmental Protection Material Location:**

Around rf shielding gasket outer perimeter

**Material:**

Rubber silicone class q environmental seal

**Material Specification:**

Zz-r-765, class 2, grade 60 federal specification single material response environmental seal

**Surface Treatment:**

Zinc emi/rfi conductor and cadmium emi/rfi conductor and copper emi/rfi conductor

**Surface Treatment Specification:**

Astm b253 assn standard 1st treatment response emi/rfi conductor and mil-c-14550, class 3 military specification 2nd treatment response emi/rfi conductor and qq-p-416, type 1, class 2 federal specification 3rd treatment response emi/rfi conductor

**Style Designator:**

Non-circular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A032a0

**Mil-std (military Standard):**

Mil-c-14550 spec.