

View Online at <https://aerobasegroup.com/nsn/5999-01-040-3655>

Cross Sectional Shape:

Mesh and composition

Hole Diameter:

Between 0.406 inches and 0.416 inches

Overall Length:

Between 13.219 inches and 13.281 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit

Overall Width:

Between 5.907 inches and 5.969 inches

Minor Width:

0.203 inches

Inside Corner Radius:

0.047 inches

Outside Corner Radius:

0.250 inches

Aperture Width:

2.437 inches

Aperture Length:

9.750 inches

Center To Center Distance Between Bolt Holes Along Width:

2.218 inches

Center To Center Distance Between Bolt Holes Along Length:

2.000 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.781 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.781 inches

Cross-sectional Height:

0.165 inches

Minor Height:

0.165 inches

Bolt Hole Quantity:

16

Environmental Protection Material Location:

Around rf shielding gasket outer perimeter

Material:

Rubber silicone class q environmental seal

Material Specification:

Zz-r-765, class 2, grade 60 federal specification single material response environmental seal

Surface Treatment:

Zinc emi/rfi conductor and cadmium emi/rfi conductor and copper emi/rfi conductor

Surface Treatment Specification:

Astm b253 assn standard 1st treatment response emi/rfi conductor and mil-c-14550, class 3 military specification 2nd treatment response emi/rfi conductor and qq-p-416, type 1, class 2 federal specification 3rd treatment response emi/rfi conductor

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-c-14550 spec.