

View Online at <https://aerobasegroup.com/nsn/5999-01-043-2099>

Body Style:

Rectangular

Hole Diameter:

0.025 inches

Body Length:

2.500 inches

Body Width:

0.560 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.320 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Mounting Facility Quantity:

2

Voltage Rating:

25.000 volts

Material And Location:

Plastic, diallyl phthalate, mil-m-14, type sgd body

Input Impedance Rating:

75.000 ohms

Output Impedance Rating:

75.000 ohms

Frequency Bandwidth:

26.0 hertz

Body Depth:

0.400 inches

Mounting Facility:

Unthreaded hole

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

1.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

300.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

0.300 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

1.000 nanoseconds

Pulse Rise Time Rating:

20.0 nanoseconds

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100