

View Online at <https://aerobasegroup.com/nsn/5999-01-047-4907>

Thread Class:

2a

Thread Pitch Diameters:

+0.1697/+0.1736 inches

Body Style:

Rectangular, front connection

Overall Depth:

6.000 inches

Frequency Rating:

Not rated

Body Length:

2.500 inches

Body Width:

2.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.000 inches

Longest Vertical Distance Between Mounting Centers:

1.500 inches

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Stud Length:

0.500 inches

Mounting Facility Quantity:

4

Voltage Rating:

300.000 volts

Material And Location:

Steel case

Input Impedance Rating:

75.000 ohms

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

5.500 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.500

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

0.025 microseconds single section and 2.075 microseconds single section

Segment Quantity Per Section:

7 single section

Segment Delay Time:

1.000 microseconds single section 1st segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

16 solder stud

Thread Size And Series/type Designator:

0.190-32 unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100