

View Online at <https://aerobasegroup.com/nsn/5999-01-049-1482>

Thread Class:

2a

Thread Pitch Diameters:

+0.0925/+0.0950 inches

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

3.960 inches

Body Width:

1.200 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.546 inches

Longest Vertical Distance Between Mounting Centers:

0.983 inches

Operating Temperature Range:

-29.0/+70.0 degrees celsius

Stud Length:

0.390 inches

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Material And Location:

Plastic body

Input Impedance Rating:

75.000 ohms

Output Impedance Rating:

75.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

0.850 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

2.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

1250.000 nanoseconds single section

Segment Quantity Per Section:

8 single section

Segment Delay Time:

550.000 nanoseconds single section 1st segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

50.0 nanoseconds

Terminal Type And Quantity:

10 pin

Thread Size And Series/type Designator:

C0.112-40 un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32100