NSN 5999-01-051-0922

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-051-0922

Body Style: Rectangular **Frequency Rating:** Not rated **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity:** 1 **Operating Tempurature Range:** -0.0/+70.0 degrees celsius **Mounting Facility Quantity:** 8 Voltage Rating: Between 2.000 volts and 5.500 volts Material And Location: Plastic, diallyl phthalate, mil-m-14, type sdg body Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated **Frequency Bandwidth:** Not rated **Body Depth:** 0.225 inches **Mounting Facility:** Pin Attenuation In Decibels: Not rated Signal Delay Method: Transmission line **Delay Time Variation Method:** Tapped **Section Delay Time:** 200.000 nanoseconds single section Segment Quantity Per Section: 5 single section Segment Delay Time: 40.000 nanoseconds single section all segments **Delay Time Variation Per Deg Celsius:**

Not rated

NSN 5999-01-051-0922

Delay Line - Page 2 of 2

Pulse Rise Time Rating:

4.0 nanoseconds

Terminal Type And Quantity:

8 tab solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100

