

View Online at <https://aerobasegroup.com/nsn/5999-01-052-0494>

**Body Style:**

Rectangular, front connection

**Overall Depth:**

0.200 inches

**Frequency Rating:**

Not rated

**Body Length:**

0.880 inches

**Body Width:**

0.260 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-62.0/+120.0 degrees celsius

**Mounting Facility Quantity:**

16

**Voltage Rating:**

Not rated

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

100.000 ohms

**Output Impedance Rating:**

100.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.180 inches

**Mounting Facility:**

Pin

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

45.000 nanoseconds single section

**Segment Quantity Per Section:**

11 single section

**Segment Delay Time:**

4.500 nanoseconds single section 6th segment err-100 and 5.500 nanoseconds single section 6th segment err-100

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

10.0 nanoseconds

**Terminal Type And Quantity:**

16 pin

**Fsc Application Data:**

Data normalizer, test set, countermeasures

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100