

View Online at <https://aerobasegroup.com/nsn/5999-01-056-1733>

Body Style:

Rectangular

Body Length:

2.000 inches

Body Width:

0.320 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

Between 1.790 inches and 1.810 inches

Shortest Horizontal Distance Between Mounting Centers:

Between 0.070 inches and 0.130 inches

Intermediate Horizontal Distance Between Mounting Centers:

0.190 mils and 0.210 centimeters

Longest Vertical Distance Between Mounting Centers:

0.380 mils and 0.620 centimeters

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Mounting Facility Quantity:

3

Voltage Rating:

100.000 pounds per hour wet

Material And Location:

Metal case

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Body Depth:

0.320 inches

Mounting Facility:

Terminal

Attenuation In Decibels:

0.500

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

1000.000 microseconds single section

Pulse Rise Time Rating:

200.0 nanoseconds

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100