

View Online at <https://aerobasegroup.com/nsn/5999-01-056-1733>

**Body Style:**

Rectangular

**Body Length:**

2.000 inches

**Body Width:**

0.320 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

Between 1.790 inches and 1.810 inches

**Shortest Horizontal Distance Between Mounting Centers:**

Between 0.070 inches and 0.130 inches

**Intermediate Horizontal Distance Between Mounting Centers:**

0.190 mils and 0.210 centimeters

**Longest Vertical Distance Between Mounting Centers:**

0.380 mils and 0.620 centimeters

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Mounting Facility Quantity:**

3

**Voltage Rating:**

100.000 pounds per hour wet

**Material And Location:**

Metal case

**Input Impedance Rating:**

500.000 ohms

**Output Impedance Rating:**

500.000 ohms

**Body Depth:**

0.320 inches

**Mounting Facility:**

Terminal

**Attenuation In Decibels:**

0.500

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

1000.000 microseconds single section

**Pulse Rise Time Rating:**

200.0 nanoseconds

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100