

View Online at <https://aerobasegroup.com/nsn/5999-01-058-2041>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.2800/+0.2801 inches

**Body Style:**

Rectangular

**Body Length:**

2.500 inches

**Body Width:**

1.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches

**Longest Vertical Distance Between Mounting Centers:**

1.000 inches

**Operating Temperature Range:**

-55.0/+95.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

100.000 pounds per hour wet

**Material And Location:**

Steel, corrosion resisting body

**Input Impedance Rating:**

500.000 ohms

**Output Impedance Rating:**

500.000 ohms

**Body Depth:**

0.500 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

1.000

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

2.500 microseconds single section

**Pulse Rise Time Rating:**

0.4 microseconds

**Terminal Type And Quantity:**

4 wire hook

**Thread Size And Series/type Designator:**

0.112-40 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100