## NSN 5999-01-058-6713



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-058-6713 **Body Style:** Rectangular, front connection **Overall Depth:** 0.435 inches **Body Length:** 0.900 inches **Body Width:** 0.400 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.700 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Inclosure Type: Encased Mounting Facility Quantity: Voltage Rating:** 3.200 volts **Material And Location:** Any acceptable body **Surface Treatment And Location:** Any acceptable body **Body Depth:** 0.300 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular Signal Delay Method: Inductance **Delay Time Variation Method: Tapped Section Delay Time:** 250.000 nanoseconds single section **Segment Quantity Per Section:** 5 single section

Segment Delay Time:

50.000 nanoseconds single section all segments

## NSN 5999-01-058-6713

Delay Line - Page 2 of 2



| P | ulse | Rise | <b>Time</b> | Rating: |  |
|---|------|------|-------------|---------|--|
|   |      |      |             |         |  |

3.0 nanoseconds

**Terminal Type And Quantity:** 

8 pin

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A32100