# NSN 5999-01-062-4993

Electrical Contact - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-01-062-4993

#### **Overall Length:**

Between 0.410 inches and 0.450 inches

#### **Overall Height:**

Between 0.024 inches and 0.026 inches

## **Overall Width:**

Between 0.040 inches and 0.050 inches

## Pin Length:

Between 0.230 inches and 0.250 inches

#### Pin Width:

Between 0.024 inches and 0.026 inches

## Current Rating In Amps:

3.0

## **Mounting Method:**

Force fit

#### Material:

Copper alloy 170 body and contact or copper alloy 172 body and contact or copper alloy 510 body and contact

## **Material Specification:**

Qq-c-533, alloy 170 federal specification 1st material response body and contact or qq-c-533, alloy 172 federal specification 2nd material response body and contact or qq-b-750, alloy cda 510, grade a federal specification 3rd material response body and contact

## **Precious Material And Location:**

Body and contact surfaces gold

#### **Precious Material And Weight:**

0.005 gold grains, troy

#### **Precious Material:**

Gold

#### Surface Treatment:

Gold body and contact and nickel body and contact and copper body and contact

## Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response body and contact and qq-n-290, class 2 federal specification 2nd treatment

response body and contact

#### Style Designator:

Post contact

## **Terminal Type And Quantity:**

1 wire wrap end opposite contact

#### Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A222a0

## Mil-std (military Standard):

Mil-g-45204 spec.