## NSN 5999-01-063-2163



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-063-2163 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** Any acceptable **Body Width:** Any acceptable **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius Voltage Rating: 5.500 volts Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** Any acceptable **Mounting Facility:** Pin **Attenuation In Decibels:** Not rated **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:** 250.000 nanoseconds single section **Segment Quantity Per Section:** 5 single section **Segment Delay Time:** 50.000 nanoseconds single section all segments **Delay Time Variation Per Deg Celsius:** Not rated **Pulse Rise Time Rating:** 4.0 nanoseconds

**Terminal Type And Quantity:** 

16 pin

## NSN 5999-01-063-2163

Delay Line - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100