Electronic Shielding Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-01-065-7033

| | s Sectional Shape: |
|--------|--|
| | angular metal |
| | Diameter: |
| | 1 inches |
| | rall Length: |
| | 20 inches |
| Ove | rall Width: |
| 16.5 | 20 inches |
| - | rture Width: |
| 15.5 | 20 inches |
| Ape | rture Length: |
| 16.8 | 20 inches |
| Cent | er To Center Distance Between Bolt Holes Along Width: |
| 3.00 | 0 inches |
| Cent | er To Center Distance Between Bolt Holes Along Length: |
| 3.00 | 0 inches |
| Outs | ide Edge To Bolt Hole Center Distance Along Width: |
| 0.38 | 0 inches |
| Outs | ide Edge To Bolt Hole Center Distance Along Length: |
| 0.38 | 0 inches |
| Cros | s-sectional Thickness: |
| 0.09 | 3 inches |
| Bolt | Hole Quantity: |
| 6 | |
| End | Application: |
| Awa | cs/e3a/411I |
| Mate | erial: |
| Silico | on |
| Style | e Designator: |
| Non- | circular |
| Shel | f Life: |
| N/a | |
| Unit | Of Measure: |
| | |
| Dem | ilitarization: |
| Yes | - demil/mli |
| Fiig: | |
| | 2a0 |