NSN 5999-01-067-1225

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-067-1225

Body Style:

Rectangular, front connection

Overall Depth:

0.495 inches

Body Length:

0.800 inches

Body Width:

0.350 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.100 inches

Operating Tempurature Range:

+0.0/+70.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Quantity:

14

Voltage Rating:

25.000 volts

Material And Location:

Plastic, epoxy resin case

Surface Treatment And Location:

Any acceptable case

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Body Depth:

0.340 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

2 position in-line

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

250.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

NSN 5999-01-067-1225

Delay Line - Page 2 of 2



Segment Delay Time:

25.000 nanoseconds single section all segments

Pulse Rise Time Rating:

42.0 nanoseconds

Terminal Type And Quantity:

14 wire leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100