## NSN 5999-01-068-9579



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-068-9579 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.900 inches **Body Width:** 0.400 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** Any acceptable **Longest Vertical Distance Between Mounting Centers:** Any acceptable **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Mounting Facility Quantity:** Voltage Rating: 5.500 volts **Material And Location:** Plastic, epoxy resin body Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.435 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** Not rated **Signal Delay Method:** Inductance **Delay Time Variation Method:** 

Tapped

Section Delay Time:

50.000 nanoseconds single section

## NSN 5999-01-068-9579

Delay Line - Page 2 of 2



## Segment Quantity Per Section: 5 single section Segment Delay Time: 10.000 nanoseconds single section all segments Delay Time Variation Per Deg Celsius: Not rated Pulse Rise Time Rating: 3.0 nanoseconds Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: -- Demilitarization:

Yes - demil/mli

**Fiig:** A32100