NSN 5999-01-068-9580



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-068-9580 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** Any acceptable **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Mounting Facility Quantity: Voltage Rating:** 5.000 volts **Material And Location:** Plastic, epoxy resin body Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.233 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** Not rated **Signal Delay Method:** Inductance **Delay Time Variation Method:**

Section Delay Time:

Tapped

100.000 nanoseconds single section

NSN 5999-01-068-9580

Delay Line - Page 2 of 2



Segment Quantity Per Section: 5 single section Segment Delay Time: 20.000 nanoseconds single section all segments Delay Time Variation Per Deg Celsius: Not rated Pulse Rise Time Rating: 4.0 nanoseconds Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: - Demilitarization:

Fiig:

A32100

Yes - demil/mli