# NSN 5999-01-068-9580

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-068-9580

**Body Style:** 

Rectangular

**Frequency Rating:** 

Not rated

# **Body Length:**

0.800 inches

#### **Body Width:**

0.400 inches

# Individual Section Quantity:

1

# Longest Horizontal Distance Between Mounting Centers:

Any acceptable

## Longest Vertical Distance Between Mounting Centers:

0.300 inches

# **Operating Tempurature Range:**

# +0.0/+70.0 degrees celsius

## **Mounting Facility Quantity:**

8

## Voltage Rating:

5.000 volts

# Material And Location:

Plastic, epoxy resin body

# Input Impedance Rating:

Not rated

# **Output Impedance Rating:**

Not rated

## Frequency Bandwidth:

Not rated

## Body Depth:

0.233 inches

## **Mounting Facility:**

Terminal

## Mounting Provision Arrangement Style:

Four position rectangular

## Attenuation In Decibels:

Not rated

# Signal Delay Method:

Inductance

# **Delay Time Variation Method:**

Tapped

#### Section Delay Time:

100.000 nanoseconds single section

# NSN 5999-01-068-9580

Delay Line - Page 2 of 2



Segment Quantity Per Section: 5 single section Segment Delay Time: 20.000 nanoseconds single section all segments Delay Time Variation Per Deg Celsius: Not rated Pulse Rise Time Rating: 4.0 nanoseconds Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: A32100